

SASSO 100 round wallwasher/floor trimless soft acoustic ceiling

048-2740614W 048-2796197 002-90776



Projet / Type _____

Notes _____

Quantité / Date _____



Général

Plafond , Encastré _____

rotation 360° _____

argent mat _____

Signal Blanc _____

IP20 _____

2770 lm _____

LED

4000 K _____

CRI \geq 90 _____

L80 / 50000 h _____

MacAdam initial \leq 2 SDCM _____

R_g: 97 , R_f: 90 , R₍₁₋₅₎: 89 _____

MR 0.81 _____

MDER 0.74 _____

Optique

wallwasher floor _____

PstLM \leq 1.0 ¹ _____

SVM \leq 0.4 ¹ _____

Electrique

DALI-2 _____

système 27.5 W _____

insert 23.4 W _____

36 Vf _____

700 mA _____

CP2 220-240V _____

système 101 lm/W² _____

insert 118 lm/W³ _____

Physique

sans bordure pour plafond acoustique _____

diamètre 114 mm _____

hauteur 96 mm _____

0.71 kg _____

Découpe

diamètre 100 mm _____


épaisseur min. du plafond 25 mm _____

épaisseur max. du plafond 40 mm _____


profondeur de l'encastrement 100 mm _____

¹ Valeur du produit contenant à pleine charge (non atténué)
² incl. optical losses and the efficiency of the operating device (converter)
³ incl. optical losses

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

