

SASSO 100 round wallwasher/floor trimless soft acoustic ceiling

048-2740519W 048-2796198 002-90777



Projet / Type _____

Notes _____

Quantité / Date _____



Général

Plafond , Encastré _____

rotation 360° _____

or , RAL260-M ¹ _____

Noir signalisation _____

IP20 _____

1970 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

MacAdam initial ≤ 2 SDCM _____

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optique

wallwasher floor _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrique

non DIM _____

système 19.2 W _____

insert 16.3 W _____

36 Vf _____

500 mA _____

CP2 220-240V _____

système 103 lm/W³ _____

insert 121 lm/W⁴ _____

Physique

sans bordure pour plafond acoustique _____

diamètre 114 mm _____

hauteur 96 mm _____

0.69 kg _____

Découpe

diamètre 100 mm _____

épaisseur min. du plafond 25 mm _____

épaisseur max. du plafond 40 mm _____

profondeur de l'encastrement 100 mm _____


¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)


³ incl. optical losses and the efficiency of the operating device (converter)

⁴ incl. optical losses

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

