



SONO LOOP IP54

surface


EN Round luminaire housing in die-cast aluminium; surface powder coated; fitted bezel in rolled, seamless welded aluminium profile; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

IT Corpo illuminante rotondo in alluminio pressofuso; verniciatura a polvere; anello in profilo di alluminio rullato e senza punti saldatura; per montaggio a parete o soffitto; diffusore satinato in PMMA a illuminazione assolutamente omogenea; stessa luminosità nei modelli di tutte le dimensioni; LED ad efficienza energetica con elevata resa cromatica; apparecchio con 2 ingressi cavi e morsetto per cablaggio passante

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
up to 133lm/W
L90 @ 50000h
non DIM, DALI-2
opal cover
IK 07, IP 54

Types



Colours



Light distribution




DiiA® standards
251, 252, 253



easy mounting by
click-mechanism



dust and insect
protection (IP54)



tunable white
2700–6500K

Order options

IP RATING

IP54

COLOUR TEMPERATURE

3000K 5
4000K 6

CONTROL

non DIM 1
DALI-2 3

MATERIAL COLOUR

○ pure white RAL 9010 7
● grey aluminium RAL 9007 D

LIGHT OPTIC COVER

opal

Options on request

COLOUR RENDERING INDEX


CRI ≥ 90

COLOUR TEMPERATURE

tunable white 2700–6500K
DALI-2 DT8

CONTROL

RCS Master (☺)
RCS Slave (☺)




SONO LOOP 260 surface



IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
7.6W	3000K	881lm	8 7 1 - 8 1 2 6 :: ◆ ◆ O
	4000K	933lm	




SONO LOOP 350 surface



IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15.9W	3000K	1940lm	8 7 1 - 8 1 3 6 :: ◆ ◆ O
	4000K	2060lm	




SONO LOOP 450 surface



IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
23.2W	3000K	2850lm	8 7 1 - 8 1 4 6 :: ◆ ◆ O
	4000K	3010lm	



SONO LOOP 600 surface



IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
43W	3000K	5410lm	8 7 1 - 8 1 5 6 :: ◆ ◆ O
	4000K	5730lm	