




Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 UGR ≤ 19 / 65° ≤ 1500 cd/m²
 L2 up to 104 lm/W
 L3 up to 111 lm/W
 L4 up to 116 lm/W
 L6 up to 117 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2

Types



Colours



Light optics



UNICO linear


recessed

EN Rectangular recessed multi-downlight made of die-cast aluminium; equipped with two (L2) / three (L3) / four (L4) / six (L6) individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high-quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering; clank-free

IT Downlight multiplo rettangolare da incasso in alluminio pressofuso; dotata di due (L2) / tre (L3) / quattro (L4) / sei (L6) lenti selezionabili individualmente o definite per applicazioni specifiche; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili; montaggio elettrico semplice grazie a collegamenti a spina a prova di polarizzazione inversa; per soffitti di spessore 2-25 mm; verniciatura a polvere; incasso possibile in vari telai; riflettore di alta qualità con superficie a microfacette e vaporizzata in alluminio; emissione precisa con diversi fasci luminosi simmetrici; o con distribuzione asimmetrica della luce; LED high power a risparmio energetico con ottima resa cromatica; senza distorsione




DiiA® standards
 251, 252, 253



one luminaire
 multiple scenes



plug / socket
 connector



black & gold
 reflector



tunable white
 2700-5000K

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

non DIM	1
DALI-2	3

LIGHT OPTIC

spot round (UGR \leq 10)	K
narrow medium round (UGR \leq 10)	N
medium round (UGR \leq 10)	B
medium square (UGR \leq 10)	E
flood round (UGR \leq 16)	C
flood square (UGR \leq 19)	F
wide flood round	D
wide flood square	G

MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	W
<input checked="" type="radio"/> jet black RAL 9005	B

LIGHT OPTIC COLOUR

chrome reflector	0
black reflector*	B

*not available for spot round, narrow medium round and wallwasher

Options on request

COLOUR TEMPERATURE

tunable white 2700–5000K

DALI-2 DT8

LIGHT OPTIC COLOUR

gold reflector

MOUNTING SET

acoustic soft ceilings

Product configurator



Create your own UNICO PRO


unico.xal.com

Planning information



The icons of the light optics are shown in the reflected ceiling plan (RCP) view.

UNICO L2 basic recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
7.3 W	up to 762lm	090-7L2:::▲0■21

choose one light optic ▲ from the options on the left depending on your room needs



WALL

2x wallwasher

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
7.3 W	645lm	090-7L2:::▲A0022



CORRIDOR

2x rectangular

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
7.3 W	643lm	090-7L2:::▲R0■21




WALL + FLOOR

2x wallwasher floor

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
7.3 W	672lm	090-7L2:::▲W0■22

UNICO L3 basic recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
9.8 W	up to 1090lm	090-7L3:::▲0■21

choose one light optic ▲ from the options on the left depending on your room needs



WALL


3x wallwasher

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
9.8 W	924lm	090-7L3:::▲A0021

Accessories

MOUNTING SET WITH TRIM


for intermediate ceilings 2–25 mm



TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L2	101-63-30	90-50	090-7L2020■
L3	138-63-30	130-50	090-7L3020■

TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25 mm



TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L2	135-47-47	90-50	090-7L20100
L3	173-47-47	130-50	090-7L30100

THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable \varnothing 4–12 mm	105-58-30	005-2531110
DALI cable \varnothing 4–12 mm	105-58-30	005-2551110

Linect® ready

LUMINOUS FLUX value calculated for
3000 K, CRI \geq 90, colour white, reflector chrome
2700 K -6%, 4000 K +7%

Order options

COLOUR TEMPERATURE ◆◆

2700K	4
3000K	5
4000K	6

CONTROL ◆

non DIM	1
DALI-2	3

LIGHT OPTIC ▲

spot round (UGR≤10)	K
narrow medium round (UGR≤10)	N
medium round (UGR≤10)	B
medium square (UGR≤10)	E
flood round (UGR≤16)	C
flood square (UGR≤19)	F
wide flood round	D
wide flood square	G

MATERIAL COLOUR ▣

○ traffic white RAL 9016	W
● jet black RAL 9005	B

LIGHT OPTIC COLOUR ■

chrome reflector	0
black reflector*	B

*not available for spot round, narrow medium round and wallwasher

Options on request

COLOUR TEMPERATURE

tunable white 2700–5000K
DALI-2 DT8

LIGHT OPTIC COLOUR

gold reflector

MOUNTING SET

acoustic soft ceilings

Product configurator




Create your own UNICO PRO
unico.xal.com

Planning information



The icons of the light optics are shown in the reflected ceiling plan (RCP) view.

UNICO L4 basic recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	up to 1520lm	090-7L4 ◆◆▲■ 21

choose one light optic ▲ from the options on the left depending on your room needs



WALL

4x wallwasher

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	1290lm	090-7L4 ◆◆▲ 021



WALL + FLOOR


4x wallwasher floor

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	1340lm	090-7L4 ◆◆▲ W0 ■ 22

Accessories

MOUNTING SET WITH TRIM


for intermediate ceilings 2–25mm



TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L4	176-63-30	165-50	090-7L4020 ▣


TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25mm



TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L4	210-47-47	165-50	090-7L40100

THROUGH WIRING CONNECTION BOX



TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø4–12mm	105-58-30	005-2531110
DALI cable ø4–12mm	105-58-30	005-2551110

Linect® ready

LUMINOUS FLUX value calculated for
 3000K, CRI ≥ 90, colour white, reflector chrome
 2700K -6%, 4000K +7%

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

non DIM	1
DALI-2	3

LIGHT OPTIC

spot round (UGR _{≤10})	K
narrow medium round (UGR _{≤10})	N
medium round (UGR _{≤10})	B
medium square (UGR _{≤10})	E
flood round (UGR _{≤16})	C
flood square (UGR _{≤19})	F
wide flood round	D
wide flood square	G

MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	W
<input checked="" type="radio"/> jet black RAL 9005	B

LIGHT OPTIC COLOUR

chrome reflector	0
black reflector*	B

*not available for spot round, narrow medium round and wallwasher

Options on request

COLOUR TEMPERATURE





tunable white 2700–5000K	
DALI-2 DT8	

LIGHT OPTIC COLOUR

gold reflector	
----------------	--

MOUNTING SET

acoustic soft ceilings	
------------------------	--



UNICO L6 basic recessed



FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
18.6 W	up to 2180lm	090-7L6:::▲0■21

choose one light optic ▲ from the options on the left depending on your room needs

WALL

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
18.6 W	1850lm	090-7L6:::▲A0021

CORRIDOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
18.6 W	1840lm	090-7L6:::▲R0■21

WALL + FLOOR

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
18.6 W	1930lm	090-7L6:::▲W0■21

Accessories

MOUNTING SET WITH TRIM

for intermediate ceilings 2–25 mm

TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L6	251-63-30	240-50	090-7L6020

TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25 mm

TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L6	285-47-47	240-50	090-7L60100

THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø4–12 mm	105-58-30	005-2531110
DALI cable ø4–12 mm	105-58-30	005-2551110

Linect® ready

LUMINOUS FLUX value calculated for
3000K, CRI≥90, colour white, reflector chrome
2700K -6%, 4000K +7%