



## Description

**EN** Round surface mounted luminaire, housing in die-cast aluminium; central decorative disc made of galvanized sheet steel attached by magnet; surface dark grey, white or black powder coated; opal cover for completely homogeneous illumination; with increased transmission and diffusion; energy-efficient LEDs with very good colour rendering; binning initial  $\leq 3$  MacAdam; available in the light colour 3000 K; CRI  $\geq 80$ ; min. 90% of the luminous flux after 50 000 hours; degree of protection IP54, with pressure compensation valve; PC I; shock resistance IK09; ambient temperatures from  $-20^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$ ;  $\varnothing 180$  mm: suitable for through wiring


**IT** Apparecchio a plafone rotondo, corpo illuminante in alluminio pressofuso; disco decorativo centrale in lamiera d'acciaio zincata fissato a magnete; superficie verniciata a polveri in grigio scuro, bianco o nero; diffusore opale per un'illuminazione omogenea; con maggiore trasmissione e diffusione; LED ad efficienza energetica con elevata resa cromatica; binning iniziale  $\leq 3$  MacAdam; disponibile in temperatura di colore 3000 K; CRI  $\geq 80$ ; min. 90% di flusso luminoso rimanente dopo 50 000 h di durata; protezione IP54, valvola di compens. pressione; classe isolamento I; resistenza all'urto IK09; temperature ambiente da  $-20^{\circ}\text{C}$  a  $+50^{\circ}\text{C}$ ;  $\varnothing 180$  mm: adatto per cablaggio passante

**DOC**  
surface

## Quickinfo

3000 K  
CRI  $\geq 80$   
L90 @ 50 000 h  
 $\varnothing 180$  up to 1340 lm  
 $\varnothing 360$  up to 2890 lm  
non DIM  
opal cover  
IK09, IP54

## Types



## Colours



## Light distribution



## Order options

### IP RATING

IP54

### COLOUR TEMPERATURE

3000K

### CONTROL

non DIM

### MATERIAL COLOUR

white  7

dark grey  D

black  8



### LIGHT OPTIC COVER

opal




## DOC 180 surface



### IP 54 LUMINAIRE

SYSTEM POWER 13 W LUMINOUS FLUX 1340lm ORDER CODE 088-271051 [↗](#)



## DOC 360 surface




### IP 54 LUMINAIRE

SYSTEM POWER 28 W LUMINOUS FLUX 2890lm ORDER CODE 088-272051 [↗](#)

### LIGHT DISTRIBUTION

opal



direct