

MOVE IN 45 round

trim

063-8121518F 063-8822117 002-90724



Progetto / Tipo
Appunti
Quantità / Data



220-240V
X-PERT
UGR ≤ 10
CRI ≥ 90
X-PERT

Generale

Soffitto , Semi-incasso
nero , RAL9005 ¹
Set di montaggio bianco traffico
IP20
1310 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam iniziale ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 88
MR 0.59
MDER 0.53

Ottico

flood
beam angle 36°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Dati elettrici

non DIM
15.9 W
inserto 13.5 W
36 Vf
400 mA
classe isolamento 2 220-240V
82 lm/W

Dati fisici


bordo
diameter 77 mm
altezza 107 mm
0.57 kg

Sagoma

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 200 mm

¹ Codice RAL
² Valore del prodotto contenitore a pieno carico (non regolato)

Distribuzione della luce



flood 36°

h (m)	E0° (lx)	ø (m)
1	3900	0.65
2	980	1.29
3	430	1.94
4	240	2.59
5	160	3.23

Disegno prodotto



Istruzioni di montaggio



Calcolatore di illuminazione

