

# MOVE IN 32 flex round

trim

063-8211518S 063-8821117 002-90742



Progetto / Tipo \_\_\_\_\_

Appunti \_\_\_\_\_

Quantità / Data \_\_\_\_\_



## Generale

Soffitto , Semi-incasso  
orientabile max 90°  
rotazione 360°  
nero , RAL9005 <sup>1</sup>  
Set di montaggio bianco traffico  
IP20  
800 lm

## LED

3000 K  
CRI ≥ 90  
L80 / 50000 h  
MacAdam iniziale ≤ 2 SDCM  
R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88  
MR 0.59  
MDER 0.53

## Ottico

spot  
beam angle 18°  
P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Dati elettrici

non DIM  
11.7 W  
inserto 8.7 W  
36 Vf  
250 mA  
classe isolamento 2 220-240V  
68 lm/W

## Dati fisici

bordo  
diameter 65 mm  
altezza 93 mm  
0.38 kg

## Sagoma

diameter 54 mm  
min. ceiling thickness 2 mm  
max. ceiling thickness 25 mm  
recessed depth 110 mm

<sup>1</sup> Codice RAL  
<sup>2</sup> Valore del prodotto contenitore a pieno carico (non regolato)

## Distribuzione della luce



spot 18°

h (m)	E0° (lx)	ø (m)
1	6060	0.32
2	1510	0.63
3	670	0.95
4	380	1.27
5	240	1.58

## Disegno prodotto



## Istruzioni di montaggio



## Calcolatore di illuminazione

