


# TASK S direct / indirect TW

## power

suspended  
059-52D503XK



Progetto / Tipo \_\_\_\_\_  
Appunti \_\_\_\_\_  
Quantità / Data \_\_\_\_\_



### Generale

Soffitto , Sospeso \_\_\_\_\_  
colori speciali \_\_\_\_\_  
IP20 \_\_\_\_\_  
indirect 1540 lm \_\_\_\_\_  
diretto 1800 lm \_\_\_\_\_  
totale 3340 lm \_\_\_\_\_

### LED

3000 K \_\_\_\_\_  
CRI ≥ 90 \_\_\_\_\_  
L90 / 50000 h \_\_\_\_\_  
sicurezza fotobio. RG 0 - Rischio esente \_\_\_\_\_  
MacAdam iniziale ≤ 3 SDCM \_\_\_\_\_  
R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_  
MR 0.61 \_\_\_\_\_  
MDER 0.55 \_\_\_\_\_

### Ottico

Microprismatic \_\_\_\_\_  
microprismatic \_\_\_\_\_  
UGR < 16 , ≥ 65° < 3000 cd/m² \_\_\_\_\_  
PstLM ≤ 1.0 <sup>1</sup> \_\_\_\_\_  
SVM ≤ 0.4 <sup>1</sup> \_\_\_\_\_

### Dati elettrici


DALI-2 \_\_\_\_\_  
27.9 W \_\_\_\_\_  
classe isolamento 1 220-240V \_\_\_\_\_  
120 lm/W \_\_\_\_\_  
1 DALI Addr. \_\_\_\_\_

### Dati fisici

cavo 1500 mm \_\_\_\_\_  
length 1448 mm \_\_\_\_\_  
width 180 mm \_\_\_\_\_  
altezza 34 mm \_\_\_\_\_  
4.1 kg \_\_\_\_\_

<sup>1</sup> Valore del prodotto contenitore a pieno carico (non regolato)

### Distribuzione della luce



### Disegno prodotto



### Istruzioni di montaggio



### Calcolatore di illuminazione

