




Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 95 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2, Casambi

Types



Colours



Light distributions



ARY rod

suspended

Decorative suspended luminaire in aluminium; surface powder coated; height adjustable U-profile pendant rod suspension (black or white), feed in U-profile; spotlight head either fixed or 265° rotatable and 90° tiltable; good glare reduction due to recessed light point plane; incl. high quality lens system; precise radiation characteristics with different beam angles; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Apparecchio a sospensione decorativo in alluminio; verniciatura a polvere; sistema a sospensione ad asta accorciabile con profilo a U (nero o bianco), cavo di alimentazione nel profilo a U; testa del faretto fissa o girevole a 265° e orientabile a 90° a scelta; ottima schermatura con superficie di emissione arretrata; incl. ottica lenticolare di qualità; curva fotometrica precisa con diversi angoli di emissione; con tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED ad efficienza energetica con elevata resa cromatica; rosone per cablaggio passante; convertitore integrato nel rosone; anelli di montaggio a soffitto per posizionare la lampada in più punti dell'ambiente disponibili come accessori



265° rotatable,
90° tiltable



free positioning by
ring and hook



track version
available

Order options

MOUNTING

- suspension 1500 mm ♂ 1
- suspension 2000 mm with hook* 2

*one ring included

COLOUR TEMPERATURE

- 2700 K 4
- 3000 K 5
- 4000 K 6

MATERIAL COLOUR

- traffic white RAL 9016 7
- jet black RAL 9005 8
- 🌈 special colours* X

*rod always in white

ACCESSORY COLOUR

- traffic white RAL 9016 7
- jet black RAL 9005 8

BEAM ANGLE

- medium 25° M
- flood 44° F



ARY rod suspended



DOWNLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.4 W 18 Vf 500 mA	791 lm	0 4 9 - 5 2 1 :: 1

ARY adjustable rod suspended



SPOTLIGHT ADJUSTABLE

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.4 W 18 Vf 500 mA	791 lm	0 4 9 - 5 3 1 :: 1

Mounting accessories

CANOPY CEILING 220–240 V AC, 50–60 Hz, □ PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
500 mA non DIM	η 79 %	115-29	0 0 5 - 2 6 0 1 1 1
500 mA DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 1 1 3
500 mA Casambi	η 85 %	115-29	0 0 5 - 2 6 0 1 1 9

use for suspension with rod

CANOPY CEILING 220–240 V AC, 50–60 Hz, □ PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
500 mA non DIM	η 79 %	115-29	0 0 5 - 2 6 0 2 1 1
500 mA DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 2 1 3
500 mA Casambi	η 85 %	115-29	0 0 5 - 2 6 0 2 1 9

use for suspension with hook

MOUNTING SET WITH TRIM for installation in ceilings from 2–25 mm

TYPE	Ø-H (mm)	ORDER CODE
single luminaire rod	77-49	0 0 5 - 3 5 2 2 0 1
single luminaire cable*	77-49	0 0 5 - 3 5 2 1 0 1

MOUNTING SET TRIMLESS for installation in plasterboard ceilings 9–25 mm

TYPE	Ø-H (mm)	ORDER CODE
single luminaire rod	75-48	0 0 5 - 3 5 1 2 0 1 7
single luminaire cable*	75-48	0 0 5 - 3 5 1 1 0 1 7

*use for suspension with hook

SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting set trimless

RING

TYPE	Ø-H (mm)	ORDER CODE
ceiling mounted	50-88	0 5 0 - 0 5 1 0 2 1

Electrical accessories

POWER SUPPLY 220–240 V AC, 50–60 Hz, □ PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
500 mA non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 3 2
500 mA DALI-2	η 82 %	147-33-23	0 0 2 - 9 0 7 3 3

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC	72-90-63	0 0 5 - 6 5 2 0 2 1 0
160 W 48 V DC constant voltage		
LED DRIVER DALI-2 DT6 1–2 addr.	36-88-59	0 0 5 - 6 1 2 1 0 3 0
200–1050 mA settable const. current		
2 × 42 W 48 V DC U _{OUT} 10–40 V		

Optical accessories see following page


INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000 K, CRI ≥ 90, colour white, lens flood 2700 K -5%, 4000 K +5%




Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 95 lm/W
 L90 @ 50 000 h
 non DIM, DALI-2, Casambi

Types



Colours



Light distributions



DESIGN
AWARD
2020




reddot winner 2020

ARY cable


suspended

EN Decorative suspended luminaire in aluminium; surface powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; good glare reduction due to recessed light point plane; high quality lens system; precise radiation characteristics with different beam angles; shades as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

IT Apparecchio a sospensione decorativo in alluminio; verniciatura a polvere; sospeso con cavo a sospensione, incl. cavo di alimentazione (nero o bianco); accorciabile a piacere; ottima schermatura con superficie di emissione arretrata; ottica lenticolare di qualità; curva fotometrica precisa con diversi angoli di emissione; paralumi come accessorio nei colori RAL velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white o signal black; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica; rosone per cablaggio passante; convertitore integrato nel rosone; anelli di montaggio a soffitto per posizionare la lampada in più punti dell'ambiente disponibili come accessori



free positioning by
ring and hook



track version
available

Order options

MOUNTING

- suspension 1500 mm 1
- suspension 2000 mm with hook* 2

*one ring included

COLOUR TEMPERATURE

- 2700 K 4
- 3000 K 5
- 4000 K 6

MATERIAL COLOUR

- traffic white RAL 9016 7
- jet black RAL 9005 8
- special colours* X

*cable always in white

SHADE COLOUR

- velvet beige RAL 085 80 10 C
- madeira brown RAL 050 40 40 T
- kingfisher grey RAL 230 60 10 L
- woodpecker olive RAL 10 50 20 G
- signal white RAL 9003 W
- signal black RAL 9004 B

ACCESSORY COLOUR

- traffic white RAL 9016 7
- jet black RAL 9005 8

BEAM ANGLE

- medium 25° M
- flood 44° F



ARY cable suspended



DOWNLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.4 W 18 Vf 500 mA	791 lm	0 4 9 - 5 8 1 1 1 1 1 1 1 1 1 1

Optical accessories

SHADE

TYPE	Ø-H (mm)	ORDER CODE
cone 300	300-188	0 4 9 - 5 9 3 3 1 1 1
cone 400	400-253	0 4 9 - 5 9 3 4 1 1 1
cone 500	500-318	0 4 9 - 5 9 3 5 1 1 1



HONEYCOMB LOUVER AND LENSES

TYPE	Ø-H (mm)	ORDER CODE
honeycomb louver	42-3	0 0 7 - 1 9 6 5 1 8 8
oval lens	42-3	0 0 7 - 1 9 6 5 8 8 0
soft lens	42-3	0 0 7 - 1 9 6 5 9 8 0
wallwasher lens	42-3	0 0 7 - 1 9 6 5 7 8 0

Mounting accessories

CANOPY CEILING 220-240V AC, 50-60Hz, PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
500 mA non DIM	η 79 %	115-29	0 0 5 - 2 6 0 2 1 1 1
500 mA DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 2 1 3 1
500 mA Casambi	η 85 %	115-29	0 0 5 - 2 6 0 2 1 9 1



MOUNTING SET RECESSED WITH TRIM

for installation in ceilings from 2-25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set with trim	77-49	0 0 5 - 3 5 2 1 0 1 1



MOUNTING SET RECESSED TRIMLESS

for installation in plasterboard ceilings 9-25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set trimless	75-48	0 0 5 - 3 5 1 1 0 1 7



SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 6 3 - 8 9 1 2 1 1 0



necessary to install mounting set trimless

RING

TYPE	Ø-H (mm)	ORDER CODE
ceiling mounted	50-88	0 5 0 - 0 5 1 0 2 1 1



Electrical accessories

POWER SUPPLY 220-240V AC, 50-60Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
500 mA non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 3 2
500 mA DALI-2	η 82 %	147-33-23	0 0 2 - 9 0 7 3 3

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240V AC 160W 48V DC constant voltage	72-90-63	0 0 5 - 6 5 2 0 2 1 0
LED DRIVER DALI-2 DT6 1-2 addr. 200-1050 mA settable const. current 2x 42W 48V DC U _{OUT} 10-40V	36-88-59	0 0 5 - 6 1 2 1 0 3 0

INSET POWER is the current consumption excluding any ballast

LUMINOUS FLUX value calculated for 3000K, CRI ≥ 90, colour white, lens flood 2700K -5%, 4000K +5%