

YAL

SASSO



SASSO 60/100 round

suspended

EN Cylindrical spotlight made of aluminium, available in 2 sizes; light inset lacquered; housing powder coated; pendant fitting with cable suspension; incl. feed (black or white); can be individually shortened; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy

IT Faretto cilindrico in alluminio, due misure; inserto verniciato; housing verniciato a polvere; sospeso con cavo a sospensione; incl. cavo di alimentazione (nero o bianco); accorciabile a piacere; emissione precisa con ottica lenticolare di alta qualità; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica; rosone per cablaggio passante; convertitore integrato nel rosone

Quickinfo

2700 K, 3000 K, 4000 K
 CRI \geq 90, 2 SDCM
 SASSO 60 up to 83lm/W
 SASSO 100 up to 98lm/W
 L80 @ 50000h
 non DIM, DALI-2

Types

suspended



Housing colours



Inset colours



Light distributions

SASSO 60



SASSO 100



glare control
 (UGR \leq 16)



easy mounting;
 no visible screws



CRI \geq 95
 2 SDCM

Order options

HOUSING HEIGHT

| | |
|--------|---|
| 75 mm | 2 |
| 150 mm | 7 |

COLOUR TEMPERATURE

| | |
|--------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| 4000 K | 6 |

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

HOUSING COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 1 |

INSET COLOUR

| | |
|--|---|
| ○ traffic white RAL 9016 (UGR _≤ 22) | 7 |
| ● matt silver (UGR _≤ 19) | 4 |
| ● jet black RAL 9005 (UGR _≤ 16) | 1 |
| ● gold dust RAL 260-M (UGR _≤ 19) | 9 |

BEAM ANGLE SASSO 60

| | |
|----------------|---|
| spot 11° | S |
| medium 21° | M |
| flood 42° | F |
| wide flood 54° | W |

BEAM ANGLE SASSO 100

| | |
|----------------|---|
| spot 19° | S |
| medium 34° | M |
| flood 45° | F |
| wide flood 65° | W |

Options on request

COLOUR RENDERING INDEX


CRI ≥ 95, 2 SDCM

MOUNTING

recessed canopy

BEAM ANGLE SASSO 100

super wide flood 70°



SASSO 60 round suspended



DOWNLIGHT

| SYSTEM POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|--------------|--------------|---------------|----------------------------|
| 11.6 W | 2700 K | 833 lm | 0 4 8 - 3 1 L 0 :: ◆ ◆ ◆ ▲ |
| | 3000 K | 901 lm | |
| | 4000 K | 968 lm | |



SASSO 100 round suspended



DOWNLIGHT

| SYSTEM POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|--------------|--------------|---------------|----------------------------|
| 20.2 W | 2700 K | 1650 lm | 0 4 8 - 3 4 2 0 :: ◆ ◆ ◆ ▲ |
| | 3000 K | 1790 lm | |
| | 4000 K | 1920 lm | |