

# SASSO 100 round wallwasher/floor

trim

048-2740519W 048-279631G 002-90779



Progetto / Tipo \_\_\_\_\_

Appunti \_\_\_\_\_

Quantità / Data \_\_\_\_\_



220-240V

360°

X-PERT

CRI ≥ 90

X-PERT

## Generale

Soffitto , Incasso

rotazione 360°

dorato , RAL260-M <sup>1</sup>

Set di montaggio alluminio bianco

IP20

1970 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

MacAdam iniziale ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f1-15</sub>: 88

MR 0.59

MDER 0.53

## Ottico

wallwasher floor

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Dati elettrici

DALI-2

19.2 W

inserto 16.3 W

36 Vf

500 mA

classe isolamento 2 220-240V

103 lm/W

inserto 121 lm/W

## Dati fisici

bordo

diameter 118 mm

altezza 96 mm

0.7 kg

## Sagoma

diameter 108 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 100 mm

<sup>1</sup> Codice RAL

<sup>2</sup> Valore del prodotto contenitore a pieno carico (non regolato)

## Distribuzione della luce



## Disegno prodotto



## Istruzioni di montaggio



## Calcolatore di illuminazione

