

SASSO 100 round downlight

trim

048-2700611F 048-2796318 002-90774



Progetto / Tipo _____

Appunti _____

Quantità / Data _____



↑ IP20
↓ IP44

220-240V

X-PERT

UGR
≤ 16

cd/m²
≤ 3000

CRI
≥ 90

X-PERT

Generale

Soffitto , Incasso _____

nero , RAL9005 ¹ _____

Set di montaggio nero intenso _____

fronte IP44 , retro IP20 _____

2200 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

MacAdam iniziale ≤ 2 SDCM _____

R_g: 97 , R_f: 90 , R_{t(1-15)}: 89 _____

MR 0.81 _____

MDER 0.74 _____

Ottico

flood _____

beam angle 45° _____

UGR < 16 , ≥ 65° < 3000 cd/m² _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Dati elettrici

non DIM _____

29.2 W _____

inserto 24.8 W _____

36 Vf _____

700 mA _____

classe isolamento 2 220-240V _____

75 lm/W _____

inserto 89 lm/W _____

Dati fisici

bordo _____

diameter 118 mm _____

altezza 75 mm _____

0.45 kg _____

Sagoma

diameter 108 mm _____

min. ceiling thickness 2 mm _____


max. ceiling thickness 25 mm _____

recessed depth 80 mm _____

¹ Codice RAL

² Valore del prodotto contenitore a pieno carico (non regolato)

Distribuzione della luce



Disegno prodotto



Istruzioni di montaggio



Calcolatore di illuminazione

