

SASSO 100 round downlight

trim

048-2700519M 048-2796318 002-90777



Progetto / Tipo _____

Appunti _____

Quantità / Data _____



↑ IP20
↓ IP44

220-240V

X-PERT

UGR
≤13

cd/m²
≤3000

CRI
≥90

X-PERT

Generale

Soffitto , Incasso _____

dorato , RAL260-M¹ _____

Set di montaggio nero intenso _____

fronte IP44 , retro IP20 _____

1450 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

MacAdam iniziale ≤ 2 SDCM _____

R_g: 100 , R_f: 91 , R₍₁₋₁₅₎: 88 _____

MR 0.59 _____

MDER 0.53 _____

Ottico

medium _____

beam angle 33° _____

UGR < 13 , ≥65° <3000 cd/m² _____

PstLM ≤ 1.0² _____

SVM ≤ 0.4² _____

Dati elettrici

non DIM _____

20.2 W _____

inserto 17.2 W _____

36 Vf _____


500 mA _____

classe isolamento 2 220-240V _____

72 lm/W _____

inserto 85 lm/W _____

Distribuzione della luce



Disegno prodotto



Dati fisici

bordo _____

diameter 118 mm _____

altezza 75 mm _____

0.47 kg _____

Sagoma

diameter 108 mm _____

min. ceiling thickness 2 mm _____

max. ceiling thickness 25 mm _____

recessed depth 80 mm _____

¹ Codice RAL

² Valore del prodotto contenitore a pieno carico (non regolato)

Istruzioni di montaggio



Calcolatore di illuminazione

