

SASSO 100 round downlight

trim

048-2700519F 048-2796318 002-90779



Progetto / Tipo
Appunti
Quantità / Data



↑ P20 ↓ P44	220-240V	X-PERT	UGR ≤ 16	cd/m ² ≤ 3000	CRI ≥ 90	MACADAM	X-PERT
----------------	----------	--------	-------------	-----------------------------	-------------	---------	--------

Generale

Soffitto , Incasso
dorato , RAL260-M ¹
Set di montaggio nero intenso
fronte IP44 , retro IP20
1630 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam iniziale ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 88
MR 0.59
MDER 0.53

Ottico

flood
beam angle 44°
UGR < 16 , ≥ 65° < 3000 cd/m ²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Dati elettrici

DALI-2
20.2 W
inserto 17.2 W
36 Vf
500 mA
classe isolamento 2 220-240V
81 lm/W
inserto 95 lm/W
1 DALI Addr.

Dati fisici

bordo
diameter 118 mm
altezza 75 mm
0.5 kg


Sagoma

diameter 108 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 80 mm


¹ Codice RAL

² Valore del prodotto contenitore a pieno carico (non regolato)

Distribuzione della luce



Disegno prodotto



Istruzioni di montaggio



Calcolatore di illuminazione

