

# SASSO 100 round downlight

trim

048-2700419F 048-279631G 002-90777



Progetto / Tipo
Appunti
Quantità / Data



↑ IP20 ↓ IP44	220-240V	X-PERT	UGR ≤ 16	cd/m <sup>2</sup> ≤ 3000	CRI ≥ 90	X-PERT
------------------	----------	--------	-------------	-----------------------------	-------------	--------

## Generale

Soffitto , Incasso
dorato , RAL260-M <sup>1</sup>
Set di montaggio alluminio bianco
fronte IP44 , retro IP20
1540 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam iniziale ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Ottico

flood
beam angle 44°
UGR < 16 , ≥ 65° < 3000 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Dati elettrici

non DIM
20.2 W
inserto 17.2 W
36 Vf
500 mA
classe isolamento 2 220-240V
76 lm/W
inserto 89 lm/W

## Dati fisici


bordo
diameter 118 mm
altezza 75 mm
0.47 kg

## Sagoma

diameter 108 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 80 mm

<sup>1</sup> Codice RAL  
<sup>2</sup> Valore del prodotto contenitore a pieno carico (non regolato)

## Distribuzione della luce



## Disegno prodotto



## Istruzioni di montaggio



## Calcolatore di illuminazione

