



## SASSO 60 round sensor/emergency

recessed

**EN** Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement


**IT** Inserto lum. rotondo (luce di emerg. o sensore); montaggio senza bisogno di utensili nel set di fissaggio (con o senza bordo perimetrale); verniciatura; incasso possibile in vari telai; inserto per luce di emerg. a LED: 3 varianti con diversi modi - Basic con pulsante di test, auto-test con LED di stato o Pro DALI con monitoraggio via DALI; sensore con controllo DALI-2: 2 varianti - Basic con sensore di luminosità e presenza o Pro con misurazione aggiuntiva di temperatura, umidità, qualità dell'aria e livello di rumore

### Quickinfo

sensor  
ESSENTIAL, SENSE  
DALI-2

emergency light  
6500 K  
CRI ≥ 80  
200 lm  
L80 @ 50000 h  
non maintained

### Types



### Housing colours



### Inset colours



### Sensors



## Order options

### INSET COLOUR

- traffic white RAL 9016 7  
 jet black RAL 9005 1

### BEAM ANGLE EMERGENCY LIGHT

- spot lens  
 escape route lens  
 anti panic lens




## Options on request

### MOUNTING SET

- acoustic soft ceilings

### INSET COLOUR

- grey, gold



## SASSO 60 sensor round



### ESSENTIAL SENSOR

**TYPE**  
 brightness & presence **ORDER CODE**  
0 48 - 2 69 3 1 1



### SENSE SENSOR

**TYPE**  
 brightness, presence, temperature,  
 sound pressure, humidity, CO<sub>2</sub> **ORDER CODE**  
0 48 - 2 69 3 1 2

## SASSO 60 emergency light round



### EMERGENCY 3h

**TYPE**  
 BASIC | 2W **ORDER CODE**  
0 48 - 2 69 3 2 1   
 SELF-TEST | 2W 0 48 - 2 69 3 2 2   
 PRO DALI | 2W 0 48 - 2 69 3 2 3

incl. 3 interchangeable lenses

## Electrical accessories

### ACCUPACK

**TYPE**  
 replacement accupack 3h **ORDER CODE**  
0 48 - 2 69 3 9 1 0

## Mounting accessories

### TRIMLESS MOUNTING SET for plasterboard ceilings 12.5/15/25 mm

**COLOUR**  
 traffic white RAL9016 **ORDER CODE**  
0 48 - 2 69 6 1 1 7

### MOUNTING SET WITH TRIM for intermediate ceilings 2-25 mm

TYPE	COLOUR	ORDER CODE
1 lamp	<input type="radio"/> traffic white RAL9016	0 48 - 2 69 6 3 1 7
	<input checked="" type="radio"/> jet black RAL 9005	0 48 - 2 69 6 3 1 8
2 lamps	<input type="radio"/> traffic white RAL9016	0 48 - 2 69 8 3 1 7
	<input checked="" type="radio"/> jet black RAL 9005	0 48 - 2 69 8 3 1 8

### TRIMLESS MOUNTING SET for soft acoustic ceilings 25-40 mm

**COLOUR**  
 signal white RAL 9003 **ORDER CODE**  
0 48 - 2 69 6 1 9 7

### MOUNTING SET WITH TRIM for soft acoustic ceilings 25-40 mm

TYPE	COLOUR	ORDER CODE
1 lamp	<input type="radio"/> signal white RAL 9003	0 48 - 2 69 6 3 9 7
	<input checked="" type="radio"/> traffic black RAL 9017	0 48 - 2 69 6 3 9 8

### MOUNTING TOOL for soft acoustic ceilings


**TYPE**  
 SASSO 60 **ORDER CODE**  
0 48 - 2 69 5 9 1 8

### CONCRETE MOUNTING HOUSING


COLOUR	L-W-H (mm)	ORDER CODE
exposed concrete ceilings	230-230-162	0 48 - 2 69 5 2 1 0
primed concrete ceilings*	614-307-120	0 48 - 2 69 5 1 1 0

\*order mounting set separately, not applicable for 2 lamps mounting set with trim


## Light distributions



emergency light  
spot lens



emergency light  
escape route lens



emergency light  
anti panic lens

