

# MOVE IN 32 round

trim

063-8111414S 063-8821117 002-90742



Progetto / Tipo \_\_\_\_\_

Appunti \_\_\_\_\_

Quantità / Data \_\_\_\_\_



## Generale

Soffitto , Semi-incasso \_\_\_\_\_

cromato \_\_\_\_\_

Set di montaggio bianco traffico \_\_\_\_\_

IP20 \_\_\_\_\_

754 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam iniziale  $\leq 2$  SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Ottico

spot \_\_\_\_\_

angolo del fascio 18° \_\_\_\_\_

PstLM  $\leq 1.0$  <sup>1</sup> \_\_\_\_\_

SVM  $\leq 0.4$  <sup>1</sup> \_\_\_\_\_

## Dati elettrici

non DIM \_\_\_\_\_

sistema 11.6 W \_\_\_\_\_

inserto 8.7 W \_\_\_\_\_

36 Vf \_\_\_\_\_

250 mA \_\_\_\_\_

classe isolamento 2 220-240V \_\_\_\_\_

sistema 65 lm/W<sup>2</sup> \_\_\_\_\_

inserto 86 lm/W<sup>3</sup> \_\_\_\_\_

## Dati fisici

bordo \_\_\_\_\_

diametro 65 mm \_\_\_\_\_

altezza 93 mm \_\_\_\_\_

0.33 kg \_\_\_\_\_

## Sagoma


diametro 54 mm \_\_\_\_\_

spessore min. del soffitto 2 mm \_\_\_\_\_

spessore max. del soffitto 25 mm \_\_\_\_\_

profondità di incasso 110 mm \_\_\_\_\_

## Distribuzione della luce



spot 18°

h (m)	E0° (lx)	ø (m)
1	5710	0.32
2	1430	0.63
3	630	0.95
4	360	1.27
5	230	1.58

## Disegno prodotto



## Istruzioni di montaggio



## Calcolatore di illuminazione

