



## MITA circle

suspended

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; either with direct or direct/indirect light distribution; energy-efficient LEDs with very good colour rendering


IT Corpo illuminante circolare in alluminio pressofuso; forma estremamente sottile; verniciatura a polvere; sospeso; con asta di sospensione accorciabile (cromata), cavo alimentazione nell'asta di sospensione; alimentatore elettronico montato nel rosone; in opzione: copertura cieca, fissata nel vano interno per mezzo di un magnete, disponibile come accessorio; riflettore ad alta lucentezza con design sfaccettato; diffusore HPO (High Performance Opal) per un'illuminazione omogenea; a scelta con emissione diretta oppure diretta/indiretta; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 80, CRI ≥ 90, 3 SDCM  
 UGR ≤ 19 / 65° ≤ 1500 cd/m<sup>2</sup>  
 up to 160 lm/W  
 L90 @ 50000h  
 DALI-2  
 reflector (UGR ≤ 19), opal

### Types


suspended



### Colours



### Light distributions



up to 160 lm/W  
 (high efficiency)



dark chrome  
 reflector option



version with  
 opal cover



magnetic  
 blind cover



DIN EN 12464-1  
 UGR ≤ 19

## Order options

### SUSPENSION

rod 1000 mm

### COLOUR TEMPERATURE

3000 K (CRI $\geq$ 90)	0
4000 K (CRI $\geq$ 90)	1
3000 K (CRI $\geq$ 80)	5
4000 K (CRI $\geq$ 80)	6

### CONTROL

DALI-2

### MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> jet black RAL 9005	8

### REFLECTOR COLOUR

<input checked="" type="checkbox"/> chrome	R
<input type="checkbox"/> dark chrome	B

### LIGHT OPTIC COVER

reflector (UGR $\leq$ 19)

opal

## Options on request



### SUSPENSION

rod 1000 mm white

rod 1000 mm black

### COLOUR TEMPERATURE

tunable white 2700–6500 K



## MITA circle 450 suspended



### REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	4210 lm	074-761133
	4000 K	4790 lm	
40 W	3000 K	5470 lm	074-762133
	4000 K	6230 lm	

### OPAL DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
24.9 W	3000 K	2760 lm	074-761133
	4000 K	3140 lm	



### REFLECTOR DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
60 W	3000 K	↓ 4170 / ± 3850 lm	074-765133
	4000 K	↓ 4750 / ± 4380 lm	

### OPAL DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
60 W	3000 K	↓ 3350 / ± 3850 lm	074-765133
	4000 K	↓ 3810 / ± 4380 lm	

## Accessories

### BLIND COVER

TYPE	ORDER CODE
MITA circle 450 suspended	074-891162